



ready-to use in minutes.

APPLICATIONS

ART AND HERITAGE

FORENSICS

VIRTUAL DISPLAY

CUSTOMIZATION

HEALTHCARE

DIGITAL ENTERTAINMENT Animation and Games

VERSATILE AND USER FRIENDLY





Hybrid structure light source technology integrating LED structured light and invisible infrared light into one device and adding advanced smart presetting in different scan modes allows 3D scanning in a broad range of applications and promotes the popularization of portable 3D scanning technology.

FAST SCANNING



Scan speed up to 1,200,000 points/s and large scan FOV of 420*440mm ensures fast 3D scanning of large size objects. The optimzied alignment algorithm enables efficient alignment despite small movements of the scanned object or person.



The software is intuitive and user-friendly. Easy operation for professional users and beginners alike. Easy to own, easy to use.







THE ERA OF SCANNING WITH HAIR ACQUISITION

The invisible infrared light source provides a reliable solution to the problem of acquiring dark-coloured objects and enables an easy acquisition of human hair.



INVISIBLE LIGHT 3D SCANNING EXPERIENCE

The new face scanning mode adopts invisible infrared light enabling a safe and comfortable scanning process





AUTHENTIC COLOR CAPTURING



FULL-COLOR REPRODUCTION

The built-in color camera supports full color texture capturing and tracking by texture.

FINE DETAILS



Impressive high resolution reaches 0.25mm. EinScan H captures the full geometry of objects such as artwork or furniture with fine details. The high accuracy of scanned data up to 0.05mm and volumetric accuracy 0.1mm/m improves the precision of 3D modeling in a dense points cloud or polygon meshes.





TECHNICAL SPECIFICATIONSEinScan H

| Scan Mode | Standard Scan | Body Scan | |
|-----------------------|--|-----------|---------------------------|
| Light Source | White Light, visible | | Infrared light, invisible |
| Safety | LED light (eye-safe) | | CLASS I (eye-safe) |
| Scan Accuracy | Up to 0.05mm | | Up to 0.6mm |
| Volumetric Accuracy* | 0.05+0.1mm/m | | / |
| Scan & Align Speed | 1,200,000points/s, 20FPS | | 720,000points/s, 20FPS |
| Align Modes | Markers-, Feature-, Hybrid- and Texture Alignment | | Feature Alignment |
| Camera Frame Rate | 55FPS | | |
| Working Distance | 470mm | | |
| Depth of Field | 200-700mm | | 200-1500mm |
| Maximum Scan Range | 420mm*440 |)mm | 780mm*900mm |
| Point distance | 0.25mm-3mm | | 0.5mm-3mm |
| Built-in Color Camera | Yes | | |
| Color Scanning | Support | | |
| Connection Standard | USB3.0 | | |
| Output Format | OBJ, STL, PLY, P3, 3MF | | |
| Dimension | 108mm*110mm*237mm | | |
| Weight | 703g | | |
| Certification | CE, FCC, ROHS, WEEE, KC | | |
| Recommend | OS:Win10, 64 bit; Graphics card: NVIDIA GTX1080 and higher; Video memory: ≥4GB; Processor: I7-8700; Memory: ≥32GB | | |

^{*} Volumetric accuracy refers to the relationship between 3D data accuracy and object size; the accuracy is reduced by 0.1mm per 100cm (standard scan & body scan). The conclusion is obtained by measuring the center of sphere under marker alignment.

